



RUBBER ROLLERS & WHEELS

Rubber Bonded Wheel



INDICATIVE PRICE

INR 320

per piece, ex-works Nashik

MINIMUM ORDER

50 Piece

MATERIALS

Nitrile (NBR), EPDM, Neoprene (CR), Natural Rubber

DESCRIPTION

Rubber Bonded Aluminium Wheels are precision-manufactured wheels with a high-quality rubber layer permanently bonded to an aluminium core. They provide excellent shock absorption, vibration damping, traction, abrasion resistance and smooth operation. Available in NR, NBR, Neoprene, EPDM, XNBR or other rubber grades with customized diameter, width, hardness and aluminium core design. These wheels are mainly used for Industrial applications. They can be ranged from 4 inches diameter to 14 inches diameter with variable thicknesses. Metal casted wheels can also be manufactured according to customer requirement.

SPECIFICATION

Wheel Type	Straight Wheel	Wheel Diameter	125 mm
Abrasive Type	Aluminium Oxide	Bond Type	Rubber Bond
Hardness Grade	Medium	Color	Black
Usage/Application	Industrial	Brand	Varsha
Bore Size	20 mm	Packaging Type	Polythene bag
Application	Grinding	Surface Material	Rubber
Wheel Material	Steel	Weight	Upto 1 kg
Diameter	Upto 100 mm		

Varsha Industries

W-20/B, M.I.D.C. Ambad, Nashik - 422010, Maharashtra, India

Phone +91 9823016609

Email varshaindustries@yahoo.com

Web varshaindustry.com

GSTIN 27AAKPC9048C1ZT